





EE-200 Electrical Tape

High quality Soft PVC Film, coated with a strong rubber based adhesive, hand applicable, 80°C.

FEATURES:

- Rubber adhesive
- PVC carrier

BENEFITS:

- Black and white
- Highly conformable
- Flame resistant
- Meet RoHS & REACH
- UL510,CSA22.2 Approved



STANDARD SIZES:

Length: 33m

Width: 19mm, 25mm Core ID: 38mm

COLORS:

Black White

Other sizes and colors are available on request.





EE-200

Properties	Value	Unit	Test Method
Total thickness	0.237-0.249	mm	ASTM D1000
Tensile strength	≥50	N/cm	ASTM D1000
Elongation at break	≥200	%	ASTM D1000
Adhesion strength			ASTM D1000
— to steel	≥2.2	N/cm	
— to backing	≥2.2	N/cm	
Flammability	B(self-extinguishing)		ISO 3795
Dielectric Strength	≥40	kV/mm	IEC 60454

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

It is specifically designed for used for wrapping electric wires and cables etc. wrapped wires with a half-lap is best, The last layer should be no tension to prevent flagging.

STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



